


Luminaire

Flumo60-S

228S-581I-090GQ/TC, B



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Linear
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
item description	R400; 90°
Dimensions	896 mm × 60 mm × 65 mm
Weight	1.8 kg
Light source	LED MODUL
Type of optical system	Microprisma, Opal diffuser
Luminous flux*	740 lm
Colour Temperature	2700 K - 6500 K Tunable White
Luminous efficacy	64 lm/W
MacAdam Light source	3
Colour rendering index	90

Luminaire power input*	11.5 W
Connection of the luminaires	DALI DT8
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 20

*±10 %

Downloads

Installation instructions



Photos



Accessories**00-00300, N**
wire suspension
2000mm**00-00301, N**
wire suspension
4000mm**00-00302, N**
wire suspension
6000mm**00-00356, K**
cable 5x0,75 4000mm**00-00357, K**
cable 5x0,75 6000mm**00-00363, K**
cable 5x1,5 2000mm**00-00370, B**
ceiling cup 80x80x32mm**228-20101, B**
2 end caps**228-20200, N**
arranging coupler