


**Luminaire**

# Flumo60-S

228S-581K-090EE/840, S



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                           |                        |
|---------------------------|------------------------|
| Type of installation      | Suspended              |
| Light distribution        | Direct-indirect        |
| Luminaire shape           | Rounded                |
| Colour of the luminaires  | Silver                 |
| Material                  | Aluminium              |
| Lifetime                  | L80/B20 50 000 hours   |
| Warranty                  | 5 years                |
| Description of luminaires | Luminaire suspended    |
| item description          | Arch R400 - 90°        |
| Dimensions                | 629 mm × 60 mm × 65 mm |
| Light source              | LED MODUL              |
| Type of optical system    | Opal diffuser          |
| Luminous flux*            | 920 lm                 |
| Colour Temperature        | 4000 K cool white      |
| Luminous efficacy         | 103 lm/W               |
| MacAdam Light source      | 3                      |
| Colour rendering index    | 80                     |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 8.9 W    |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-00300, N**  
wire suspension  
2000mm**00-00301, N**  
wire suspension  
4000mm**00-00302, N**  
wire suspension  
6000mm**00-00352, K**  
cable 3x0,75 2000mm**00-00358, K**  
cable 3x0,75 4000mm**00-00360, K**  
cable 3x0,75 6000mm**00-00370, S**  
ceiling cup 80x80x32mm**228-20101, S**  
2 end caps**228-20200, N**  
arranging coupler