


**Luminaire**

# Flumo60-S

**228S-5C1K-120GD/840, W**


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Rounded
Colour of the luminaires	White
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
item description	Arch R758 - 120°
Dimensions	1587 mm × 60 mm × 65 mm
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	4560 lm
Colour Temperature	4000 K cool white
Luminous efficacy	115 lm/W
MacAdam Light source	3
Colour rendering index	80

Luminaire power input\* 39.7 W

---

Connection of the luminaires DALI

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-00300, N**  
wire suspension  
2000mm**00-00301, N**  
wire suspension  
4000mm**00-00302, N**  
wire suspension  
6000mm**00-00356, K**  
cable 5x0,75 4000mm**00-00357, K**  
cable 5x0,75 6000mm**00-00363, K**  
cable 5x1,5 2000mm**00-00370, W**  
ceiling cup 80x80x32mm**228-20101, W**  
2 end caps**228-20200, N**  
arranging coupler