



## Luminaire

# Flumo60-S

228S-5D1I-060GD/840, B



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                           |                            |
|---------------------------|----------------------------|
| Type of installation      | Suspended                  |
| Light distribution        | Direct-indirect            |
| Luminaire shape           | Rounded                    |
| Colour of the luminaires  | Black                      |
| Material                  | Aluminium                  |
| Lifetime                  | L80/B20 50 000 hours       |
| Warranty                  | 5 years                    |
| Description of luminaires | Luminaire suspended        |
| item description          | Arch R1025 - 60°           |
| Dimensions                | 1074 mm × 60 mm × 65 mm    |
| Light source              | LED MODUL                  |
| Type of optical system    | Microprisma, Opal diffuser |
| Luminous flux*            | 1990 lm                    |
| Colour Temperature        | 4000 K cool white          |
| Luminous efficacy         | 81 lm/W                    |
| MacAdam Light source      | 3                          |
| Colour rendering index    | 80                         |

Luminaire power input\* 24.7 W

---

Connection of the luminaires DALI

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-00300, N**  
wire suspension  
2000mm**00-00301, N**  
wire suspension  
4000mm**00-00302, N**  
wire suspension  
6000mm**00-00356, K**  
cable 5x0,75 4000mm**00-00357, K**  
cable 5x0,75 6000mm**00-00363, K**  
cable 5x1,5 2000mm**00-00370, B**  
ceiling cup 80x80x32mm**228-20101, B**  
2 end caps**228-20200, N**  
arranging coupler