



Luminaire

Flumo60-S

228S-5D1I-120GD/830, S



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation Suspended

Light distribution Direct-indirect

Luminaire shape Rounded

Colour of the luminaires Silver

Material Aluminium

Lifetime L80/B20 50 000 hours

Warranty 5 years

Description of luminaires Luminaire suspended

item description Arch R1025 - 120°

Dimensions (w × h mm) 60 mm × 65 mm

Diameter ø 1025

Angle 120 °

Light source LED MODUL

DIR optical system Microprisma

INDIR optical system Opal cover

Luminous flux* 4710 lm

Colour Temperature 3000 K warm white

Luminous efficacy 86 lm/W

MacAdam Light source 3

Colour rendering index 80

Luminaire power input*	54.9 W
Connection of the luminaires	DALI
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 20

*±10 %

Downloads

[Installation instructions](#)[Photos](#)

Accessories



00-00300, N
wire suspension
2000mm



00-00301, N
wire suspension
4000mm



00-00302, N
wire suspension
6000mm



00-00356, K
cable 5x0,75 4000mm,
transparent



00-00357, K
cable 5x0,75 6000mm,
transparent



00-00363, K
cable 5x1,5 2000mm



00-00370, S
ceiling cup 80x80x32mm



228-20101, S
2 end caps



228-20200, N
arranging coupler