


**Luminaire**

# Flumo60-S

**228S-XXXI-XXGXE/840, B**


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                                   |                        |
|-----------------------------------|------------------------|
| Type of installation              | Suspended              |
| Light distribution                | Direct                 |
| Luminaire shape                   | Other shape            |
| Colour of the luminaires          | Black                  |
| Material                          | Aluminium              |
| Lifetime                          | L80/B20 50 000 hours   |
| Warranty                          | 5 years                |
| Description of luminaires         | Luminaire suspended    |
| item description                  | Arch Rxxx - Y°         |
| Dimensions                        | 315 mm × 60 mm × 65 mm |
| Type of optical system            | Microprisma            |
| Luminous flux*                    | 455 lm - 4020 lm       |
| Colour Temperature                | 4000 K cool white      |
| Luminous efficacy                 | 95 lm/W                |
| MacAdam Light source              | 3                      |
| Colour rendering index            | 80                     |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 99                     |

Luminaire power input\* 4.8 W - 43 W

---

Connection of the luminaires ON/OFF

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

