


**Luminaire**

# Shift-C

26-500F-10GGD/930, S



|                           |                                          |
|---------------------------|------------------------------------------|
| Type of installation      | Suspended                                |
| Light distribution        | Direct                                   |
| Luminaire shape           | Circular                                 |
| Colour of the luminaires  | Silver                                   |
| Material                  | Aluminium                                |
| Lifetime                  | L80/B20 50 000 hours                     |
| Warranty                  | 5 years                                  |
| Description of luminaires | Luminaire suspended                      |
| item description          | Silver ceiling cup and transparent cable |
| Dimensions                | ø 85 mm × 200 mm                         |
| Weight                    | 1.38 kg                                  |
| Light source              | LED MODUL                                |

**Technical drawing**


|                        |                   |
|------------------------|-------------------|
| DIR optical system     | Reflector         |
| Luminous flux*         | 1720 lm           |
| Colour Temperature     | 3000 K warm white |
| Luminous efficacy      | 99 lm/W           |
| MacAdam Light source   | 3                 |
| Colour rendering index | 90                |
| Beam angle             | 32°               |

## Curve



Luminaire power input\* 17.3 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-01000**  
reflector 18°**00-01001**  
reflector 25°**00-01002**  
reflector 32°**00-01003**  
reflector 52°**00-01100**  
Satinice diffuser**00-01101**  
Linear optic