


**Luminaire**

# Shift

26-500U-30GDD/940, B



Designer Kryštof Nosál has created a luminaire with unrivalled variability. In addition, the Shift family of single luminaires allows for any method of installation. You can choose between a semi-recessed, surface and pendant version. The spot LED luminaire consists of 1, 2, 3 or 5 light sources, which can be moved along the axis of the luminaire body, tilted up to an angle of 45° and rotated up to 355°. The luminaire has 4 beam angles of 15°, 25°, 36°, 60°.

Design Kryštof Nosál

**Technical drawing**


|                                   |                             |
|-----------------------------------|-----------------------------|
| Type of installation              | Suspended                   |
| Light distribution                | Direct                      |
| Luminaire shape                   | Rounded                     |
| Colour of the luminaires          | Black                       |
| Material                          | Aluminium                   |
| Lifetime                          | L80/B20 50 000 hours        |
| Warranty                          | 5 years                     |
| Description of luminaires         | Luminaire suspended         |
| item description                  | Black ceiling cup and cable |
| Dimensions (l × w × h mm)         | 720 mm × 85 mm × 92 mm      |
| Light source                      | LED MODUL                   |
| DIR optical system                | Reflector                   |
| Luminous flux*                    | 1060 lm                     |
| Colour Temperature                | 4000 K cool white           |
| Luminous efficacy                 | 114 lm/W                    |
| MacAdam Light source              | 3                           |
| Colour rendering index            | 90                          |
| Beam angle                        | 25°                         |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 14.9                        |

## Curve



Luminaire power input\* 27.9 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-01000**  
reflector 18°**00-01001**  
reflector 25°**00-01002**  
reflector 32°**00-01003**  
reflector 52°**00-01100**  
Satinice diffuser**00-01101**  
Linear optic