



## Luminaire

# Rundo 24

290-240K-10GGD/830, W



Circular luminaires with an aluminium profile come in height 24 mm. Rundo24 luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|  |  |
|--|--|
| Type of installation                   | Surface, Wall mounted, Suspended         |
| Light distribution                     | Direct                                   |
| Luminaire shape                        | Circular                                 |
| Colour of the luminaires               | White                                    |
| Material                               | Aluminium                                |
| Lifetime                               | L80/B20 50 000 hours                     |
| Warranty                               | 5 years                                  |
| Description of luminaires              | Luminaire surface/wall mounted/suspended |
| Dimensions                             | ø 410 mm × 24 mm                         |
| Weight                                 | 3.4 kg                                   |
| Light source                           | LED MODUL                                |
| Type of optical system                 | Opal diffuser                            |
| Luminous flux                          | 2510 lm ± 10 %                           |
| Colour Temperature                     | 3000 K warm white                        |
| Luminous efficacy                      | 132 lm/W                                 |
| MacAdam Light source                   | 3  |
| Colour rendering index                 | 80                                       |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 23.4                                     |

## Curve



Luminaire power input 19 W  $\pm$  10 %

Connection of the luminaires DALI dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

## Downloads

Installation instructions



Photos

