



## Luminaire

# Rundo 24

290-250K-10GEM3/830, B



Circular luminaires with an aluminium profile come in height 24 mm. Rundo24 luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|                              |                                |
|------------------------------|--------------------------------|
| Type of installation         | Surface, Wall mounted          |
| Light distribution           | Direct                         |
| Luminaire shape              | Circular                       |
| Colour of the luminaires     | Black                          |
| Material                     | Aluminium                      |
| Lifetime                     | L80/B20 50 000 hours           |
| Warranty                     | 2 years                        |
| Description of luminaires    | Luminaire surface/wall mounted |
| Dimensions                   | ø 501 mm × 24 mm               |
| Light source                 | LED MODUL                      |
| DIR optical system           | Opal diffuser                  |
| Luminous flux*               | 1860 lm                        |
| Colour Temperature           | 3000 K warm white              |
| Luminous efficacy            | 116 lm/W                       |
| MacAdam Light source         | 3                              |
| Colour rendering index       | 80                             |
| Luminaire power input*       | 16 W                           |
| Connection of the luminaires | ON/OFF + 3h emergency          |
| Electrical voltage           | 220-240V                       |
| Frequency                    | 50/60Hz                        |

 **CE IP 40**

\*±10 %

## Downloads

Installation instructions



Photos

