



## Luminaire

# Rundo 24

290-280K-10GEM3/830, B +  
00-00334, B



Circular luminaires with an aluminium profile come in height 24 mm. Rundo24 luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

|                              |                             |
|------------------------------|-----------------------------|
| Type of installation         | Suspended                   |
| Light distribution           | Direct                      |
| Luminaire shape              | Circular                    |
| Colour of the luminaires     | Black                       |
| Material                     | Aluminium                   |
| Lifetime                     | L80/B20 50 000 hours        |
| Warranty                     | 2 years                     |
| Description of luminaires    | Luminaire suspended         |
| item description             | Black ceiling cup and cable |
| Dimensions                   | ø 804 mm × 24 mm            |
| Light source                 | LED MODUL                   |
| DIR optical system           | Opal diffuser               |
| Luminous flux*               | 3510 lm                     |
| Colour Temperature           | 3000 K warm white           |
| Luminous efficacy            | 139 lm/W                    |
| MacAdam Light source         | 3                           |
| Colour rendering index       | 80                          |
| Luminaire power input*       | 25.3 W                      |
| Connection of the luminaires | ON/OFF + 3h emergency       |
| Electrical voltage           | 220-240V                    |
| Frequency                    | 50/60Hz                     |

 **CE** IP 40

\*±10 %

Technical drawing



## Downloads

[Installation instructions](#)[Photos](#)