



## Luminaire


# Rundo 24

290-281I-10GED/830, W



Circular luminaires with an aluminium profile come in height 24 mm. Rundo24 luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|                           |                                |
|---------------------------|--------------------------------|
| Type of installation      | Surface, Wall mounted          |
| Light distribution        | Direct-indirect                |
| Luminaire shape           | Circular                       |
| Colour of the luminaires  | White                          |
| Material                  | Aluminium                      |
| Lifetime                  | L80/B20 50 000 hours           |
| Warranty                  | 5 years                        |
| Description of luminaires | Luminaire surface/wall mounted |
| Dimensions                | ø 804 mm × 24 mm               |
| Light source              | LED MODUL                      |
| DIR optical system        | Microprisma                    |
| INDIR optical system      | Opal cover                     |
| Luminous flux*            | 4040 lm                        |
| Colour Temperature        | 3000 K warm white              |
| Luminous efficacy         | 149 lm/W                       |
| MacAdam Light source      | 3                              |
| Colour rendering index    | 80                             |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 27.2 W   |
| Connection of the luminaires | DALI     |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

  IP 40

\*±10 %

## Downloads

[Installation instructions](#)[Photos](#)