


**Luminaire**

# Rundo 24

290-281K-10GHM3/840, W +  
00-00334, W



Circular luminaires with an aluminium profile come in height 24 mm. Rundo24 luminaires feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

|                           |                             |
|---------------------------|-----------------------------|
| Type of installation      | Suspended                   |
| Light distribution        | Direct-indirect             |
| Luminaire shape           | Circular                    |
| Colour of the luminaires  | White                       |
| Material                  | Aluminium                   |
| Lifetime                  | L80/B20 50 000 hours        |
| Warranty                  | 2 years                     |
| Description of luminaires | Luminaire suspended         |
| item description          | White ceiling cup and cable |
| Dimensions                | ø 804 mm × 24 mm            |
| Light source              | LED MODUL                   |
| DIR optical system        | Opal diffuser               |
| INDIR optical system      | Opal cover                  |
| Luminous flux*            | 8030 lm                     |
| Colour Temperature        | 4000 K cool white           |
| Luminous efficacy         | 145 lm/W                    |
| MacAdam Light source      | 3                           |
| Colour rendering index    | 80                          |

## Technical drawing



Luminaire power input\* 55.2 W

Connection of the luminaires ON/OFF + 3h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\* $\pm 10\%$

## Downloads

Installation instructions



Photos

