



## Luminaire

# Ravo-C

55-283K-10GDM/840, W



## Technical drawing



|                                   |                             |
|-----------------------------------|-----------------------------|
| Type of installation              | Surface, Suspended          |
| Light distribution                | Direct                      |
| Luminaire shape                   | Circular                    |
| Colour of the luminaires          | White                       |
| Material                          | Aluminium/Plastic           |
| Lifetime                          | L80/B20 50 000 hours        |
| Warranty                          | 2 years                     |
| Description of luminaires         | Luminaire surface/suspended |
| Dimensions                        | ø 172 mm × 187 mm           |
| Light source                      | LED MODUL                   |
| DIR optical system                | Opal diffuser               |
| Luminous flux*                    | 1130 lm                     |
| Colour Temperature                | 4000 K cool white           |
| Luminous efficacy                 | 118 lm/W                    |
| MacAdam Light source              | 3                           |
| Colour rendering index            | 80                          |
| Beam angle                        | 64°                         |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 19                          |

## Curve



Luminaire power input\* 9.6 W

Connection of the luminaires ON/OFF + 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00399, W**  
suspension set  
2000mm, 1 pcs.of  
wires, cable  
5x0,75mm, ceiling  
cup