



Luminaire

Basi 2.0

71-008U-10GDV/930, B +
00-00156E




We have expanded the Basi family with new small siblings. We offer the new additions in white at no extra charge. They achieve maximum luminous fluxes of 650 lm and 1500 lm and a colour rendering index of Ra90. These unobtrusive but efficient downlights have beam angles of 15°, 24°, 36° (40°).

Technical drawing


Type of installation	Recessed
Light distribution	Direct
Luminaire shape	Circular
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L70/B50 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire recessed
item description	Basi 2.0 - 50 mm
Dimensions	ø 83 mm × 79 mm
Weight	0.25 kg
Light source	LED MODUL
DIR optical system	MEDIUM - middle angle
Luminous flux*	1230 lm
Colour Temperature	3000 K warm white
Luminous efficacy	96 lm/W
MacAdam Light source	3
Colour rendering index	90
Beam angle	24°

Curve



Luminaire power input* 12.8 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

 **CE** IP 20

*±10 %

Downloads

Installation instructions



Photos

