



## Luminaire

# Styrk

86-500D-20GGE/830, W



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



Type of installation	Suspended
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	White
Material	Aluminium
Lifetime	L90/B50 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
item description	White ceiling cup and cable
Dimensions (l × w × h mm)	1127 mm × 56 mm × 58 mm
Light source	LED MODUL
DIR optical system	Asymmetric reflector
Luminous flux* při 25°C	2610 lm
Colour Temperature	3000 K warm white
Luminous efficacy	118 lm/W
MacAdam Light source	3
Colour rendering index	80

Luminaire power input*	22.1 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 54

\*±10 %

## Downloads

[Installation instructions](#)[Photos](#)