



## Luminaire

# Styrk

86-500D-30GHD/830, S



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



|                           |  |
|---------------------------|--|
| Type of installation      | Suspended                                |
| Light distribution        | Direct                                   |
| Luminaire shape           | Linear                                   |
| Colour of the luminaires  | Silver                                   |
| Material                  | Aluminium                                |
| Lifetime                  | L80/B10 70 000 hours                     |
| Warranty                  | 5 years                                  |
| Description of luminaires | Luminaire suspended                      |
| item description          | Silver ceiling cup and transparent cable |
| Dimensions (l × w × h mm) | 1688 mm × 56 mm × 58 mm                  |
| Light source              | LED MODUL                                |
| DIR optical system        | Asymmetric reflector                     |
| Luminous flux* při 25°C   | 6470 lm                                  |
| Colour Temperature        | 3000 K warm white                        |
| Luminous efficacy         | 117 lm/W                                 |
| MacAdam Light source      | 3  |
| Colour rendering index    | 80                                       |

Luminaire power input\* 55.3 W

---

Connection of the luminaires DALI

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 54

\*±10 %

## Downloads

Installation instructions



Photos

