



## Luminaire

# Styrk

86-500I-20GGE/840, S



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



|                           |  |
|---------------------------|--|
| Type of installation      | Suspended                                |
| Light distribution        | Direct                                   |
| Luminaire shape           | Linear                                   |
| Colour of the luminaires  | Silver                                   |
| Material                  | Aluminium                                |
| Lifetime                  | L90/B50 50 000 hours                     |
| Warranty                  | 5 years                                  |
| Description of luminaires | Luminaire suspended                      |
| item description          | Silver ceiling cup and transparent cable |
| Dimensions (l × w × h mm) | 1127 mm × 56 mm × 58 mm                  |
| Light source              | LED MODUL                                |
| DIR optical system        | Microprisma                              |
| Luminous flux* při 25°C   | 2820 lm                                  |
| Colour Temperature        | 4000 K cool white                        |
| Luminous efficacy         | 128 lm/W                                 |
| MacAdam Light source      | 3  |
| Colour rendering index    | 80                                       |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 22.1 W   |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

  IP 54

\*±10 %

## Downloads

Installation instructions



Photos

