



Luminaire

Styrk

86-500K-40GGD/830, B



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

Technical drawing



Type of installation	Suspended
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L90/B50 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions	2249 mm × 56 mm × 58 mm
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux* při 25°C	6110 lm
Colour Temperature	3000 K warm white
Luminous efficacy	146 lm/W
MacAdam Light source	3
Colour rendering index	80
Luminaire power input*	41.8 W
Connection of the luminaires	DALI
Electrical voltage	220-240V
Frequency	50/60Hz

⊕ IP 54

*±10 %

Downloads

Installation instructions



Photos

