



## Luminaire

# Styrk

86-500K-40GGM/830, B



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



|                           |                             |
|---------------------------|-----------------------------|
| Type of installation      | Suspended                   |
| Light distribution        | Direct                      |
| Luminaire shape           | Linear                      |
| Colour of the luminaires  | Black                       |
| Material                  | Aluminium                   |
| Lifetime                  | L90/B50 50 000 hours        |
| Warranty                  | 2 years                     |
| Description of luminaires | Luminaire suspended         |
| item description          | Black ceiling cup and cable |
| Dimensions (l × w × h mm) | 2249 mm × 56 mm × 58 mm     |
| Light source              | LED MODUL                   |
| DIR optical system        | Opal diffuser               |
| Luminous flux* při 25°C   | 6110 lm                     |
| Colour Temperature        | 3000 K warm white           |
| Luminous efficacy         | 146 lm/W                    |
| MacAdam Light source      | 3                           |
| Colour rendering index    | 80                          |

|                              |                       |
|------------------------------|-----------------------|
| Luminaire power input*       | 41.8 W                |
| Connection of the luminaires | ON/OFF + 1h emergency |
| Electrical voltage           | 220-240V              |
| Frequency                    | 50/60Hz               |

 **CE** IP 54

\*±10 %

## Downloads

Installation instructions



Photos

