



## Luminaire

# Styrk

86-500Q-20GHE/830, W



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



|                              |                             |
|------------------------------|-----------------------------|
| Type of installation         | Suspended                   |
| Light distribution           | Direct                      |
| Luminaire shape              | Linear                      |
| Colour of the luminaires     | White                       |
| Material                     | Aluminium                   |
| Lifetime                     | L80/B10 70 000 hours        |
| Warranty                     | 5 years                     |
| Description of luminaires    | Luminaire suspended         |
| item description             | White ceiling cup and cable |
| Dimensions<br>(l × w × h mm) | 1127 mm × 56 mm × 58 mm     |
| Light source                 | LED MODUL                   |
| DIR optical system           | Batwing                     |
| Luminous flux*<br>při 25°C   | 4960 lm                     |
| Colour Temperature           | 3000 K warm white           |
| Luminous efficacy            | 132 lm/W                    |
| MacAdam Light source         | 3                           |
| Colour rendering index       | 80                          |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 37.7 W   |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

  IP 54

\*±10 %

## Downloads

Installation instructions



Photos

