



## Family

# Legio

We have designed the Legio luminaire in cooperation with Belgian designer Serge Cornelissen, who came up with an interesting idea of two identical luminaires in two different coats. These consist of an outer aluminium profile painted in white, black or silver and an aluminium profile painted in a special white colour. Its shape variations evoke basic geometric shapes that will make us reminisce about geometry lessons in the third grade of our primary school, where these luminaires definitely belong and can be used as an admissible cheat sheet. The variety of shapes and, last but not least, the excellent parameters of 130 lm/W and UGR

Type of installation	Suspended
Light distribution	Direct-indirect
Colour of the luminaires	Black, Silver, White
Colour Temperature	3000 K warm white, 4000 K cool white
Material	Aluminium
Light source	LED MODUL
MacAdam Light source	2
Connection of the luminaires	ON/OFF
Lifetime	L90/B50 50 000 hours
Warranty	5 years

## Luminaire family variants Legio



## Legio

### Assembly



### Light distribution



### Energy class

energy\_class\_g

### Marks

Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
123-501K-20GEE/840, W	1130 × 170 × 40	23.3	2940	4000	< 22
123-501K-20GGE/840, W	1130 × 170 × 40	38.8	4530	4000	< 23.5
123-501K-25GEE/840, W	1410 × 170 × 40	31.1	3950	4000	< 21.6
123-501K-25GGE/840, W	1410 × 170 × 40	50.8	6080	4000	< 23.1
123-501K-30GEE/840, W	1690 × 170 × 40	38.8	4960	4000	< 21.4
123-501K-30GGE/840, W	1690 × 170 × 40	63.5	7630	4000	< 22.9
123-501K-40GEE/840, W	2250 × 170 × 40	54.4	6970	4000	< 21.1
123-501K-40GGE/840, W	2250 × 170 × 40	88.9	10730	4000	< 22.6

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.

## Notes

Colour of the  
luminaires



Colour Temperature

3000 K warm white  
4000 K cool white

Optic system

Microprisma  
Opal diffuser

Connection of the  
luminaires

ON/OFF

Ra

80

Luminaires come complete with all necessary accessories.

## Legio

### Assembly



### Light distribution




### Energy class

energy\_class\_g

### Marks









Code	Dimensions l/w/h (mm)	Power of the luminaire (W)	Luminous flux (lm)	Colour Temperature (K)	UGR
123-551K-20GEE/840, W	1130 × 170 × 40	23.3	2940	4000	< 22
123-551K-20GGE/840, W	1130 × 170 × 40	38.8	4530	4000	< 23.5
123-551K-25GEE/840, W	1410 × 170 × 40	31.1	3950	4000	< 21.6
123-551K-25GGE/840, W	1410 × 170 × 40	50.8	6080	4000	< 23.1
123-551K-30GEE/840, W	1690 × 170 × 40	38.8	4960	4000	< 21.4
123-551K-30GGE/840, W	1690 × 170 × 40	63.5	7630	4000	< 22.9
123-551K-40GEE/840, W	2250 × 170 × 40	54.4	6970	4000	< 21.1
123-551K-40GGE/840, W	2250 × 170 × 40	88.9	10730	4000	< 22.6

AnThese codes represent white luminaires with chromaticity temperature 4000K and opal diffuser.




Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF
	Ra	80
Luminaires come complete with all necessary accessories.		

## Legend



### Type of installation

	Recessed lights		Wall mounted lights
	Semi-recessed luminaire		Suspended lights
	Surface lights		Free-standing lights
	3 circuit track lights		Table lamp lights







### Light distribution

	Direct luminaire
	Direct-indirect luminaire
	Indirect luminaire

### Light source

	<b>Tunable White</b> adjusting the color temperature		<b>RealWhite</b> true display of white color
	<b>RealColour</b> true display of colors Ra≥97		<b>StrongColour</b> highlight one color

### Marks

	Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
	European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
	Luminaires are certified according to the European ENEC system
	Recommended mounting hole size

**IPxy** IP code indicating the degree of protection of live parts

**EAC** Eurasian Conformity

## 11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

**Optic system**

**Electrical connection**

**Colour**












### Optic system

<b>B</b>	Microprismatic system, low UGR	<b>L</b>	Plain aluminium reflector
<b>C</b>	Clear cover	<b>M</b>	Matt parabolic louvre
<b>D</b>	Asymmetric reflector	<b>S</b>	SPOT - narrow angle
<b>E</b>	Polished parabolic louvre, high LOR	<b>U</b>	MEDIUM - middle angle
<b>F</b>	FLOOD - wide angle	<b>W</b>	Wide beam angle
<b>I</b>	Microprismatic optical system	<b>Z</b>	Plastic louver, low UGR
<b>K</b>	Opal diffuser		




### Electrical connection

<b>/BT</b>	Luminaires controlled via Bluetooth technology	<b>P</b>	Sensor and electronic ballast
<b>D</b>	DALI dimmable	<b>T</b>	By switch dimmable (touch dimm)
<b>E</b>	Electronic ballast non-dimmable	<b>TD</b>	DALI or by switch (touch dimm) dimmable
<b>M</b>	Electronic ballast non-dimmable with 1h emergency	<b>U</b>	Dimmable luminaire with dimmer on the luminaire
<b>M3</b>	Electronic ballast non-dimmable with 3h emergency		

### Colour

<b>W</b>	 RAL 9003	<b>B</b>	 RAL 9005	<b>S</b>	 TIGER 09/90530
<b>1021</b>	 RAL 1021	<b>2000</b>	 RAL 2000	<b>3020</b>	 RAL 3020
<b>5015</b>	 RAL 5015	<b>6018</b>	 RAL 6018	<b>7016</b>	 RAL 7016
<b>9006</b>	 RAL 9006	<b>9010</b>	 RAL 9010		

### Značky typu

	Smart – Luminaire or the lighting system controlled by motion, daylight or via smart devices using Bluetooth technology
	Acoustic – Luminaire with acoustic absorption properties which reduce disturbing noise and improve the acoustics of the room
	Multiwatt – Luminaires with individually adjustable luminous flux using a special antenna or mobile application

**UGR** UGR – The luminaire suitable for office spaces