



## Family


# Lina35-S

The linear system luminaires of the Lina35-S family provide one of the thinnest profiles in our product range. The luminaires with direct distribution of light are available in the pendant, surface, and recessed versions for ceiling installations and can also be mounted on the wall. In any case, you can line the luminaires up in a row thus creating the ideal length to meet your needs. Thanks to the option to extend and retract the opal diffuser, you can find the ideal combination of lights for a specific interior according to your needs. Thanks to this variability, Lina35-S can be used in virtually any area, but especially in the social, public and commercial ones. Luminaires with an extended diffuser diffuse their light into a significantly larger area thus helping to soften the entire interior.

## Luminaire family variants Lina35-S



## Lina35-S



Assembly

Light distribution


Energy class

Marks

### Notes

End caps, suspensions, supply cables, and ceiling cup for luminaires must be ordered separately. To connect into systems, please order the respective number of couplers.

## Lina35-S



Assembly

Light distribution


Energy class

Marks

### Notes

End caps, suspensions, supply cables, and ceiling cup for luminaires must be ordered separately. To connect into systems, please order the respective number of couplers.

## Lina35-S



Assembly


Light distribution

Energy class

Marks

**Notes** The appropriate quantity of terminals must be ordered for the luminaires. Order the appropriate quantity of connectors for connecting in the series.

## Lina35-S



Assembly

Light distribution

Energy class

Marks

**Notes** The appropriate quantity of terminals must be ordered for the luminaires. Order the appropriate quantity of connectors for connecting in the series.

## Accessories



Code	Description
00-00350, K	cable 3x0,75 1000mm, transparent
00-00352, K	cable 3x0,75 2000mm, transparent
00-00354, K	cable 5x0,75 1000mm, transparent
00-00355, K	cable 5x0,75 2000mm, transparent
00-00356, K	cable 5x0,75 4000mm, transparent
00-00357, K	cable 5x0,75 6000mm, transparent
00-00358, K	cable 3x0,75 4000mm, transparent
00-00360, K	cable 3x0,75 6000mm, transparent



Code	Description
00-00370, W	ceiling cup 80x80x32mm

Notes

Accessories colour



## Legend

### Type of installation

	Recessed lights		Wall mounted lights
	Semi-recessed luminaire		Suspended lights
	Surface lights		Free-standing lights
	3 circuit track lights		Table lamp lights

### Light distribution

	Direct luminaire
	Direct-indirect luminaire
	Indirect luminaire

### Light source

	<b>Tunable White</b> adjusting the color temperature		<b>RealWhite</b> true display of white color
	<b>RealColour</b> true display of colors Ra≥97		<b>StrongColour</b> highlight one color

### Marks

	Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
	European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
	Luminaires are certified according to the European ENEC system
	Recommended mounting hole size

**IPxy** IP code indicating the degree of protection of live parts

**EAC** Eurasian Conformity

## 11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

**Optic system**

**Electrical connection**

**Colour**

### Optic system

<b>B</b>	Microprismatic system, low UGR	<b>L</b>	Plain aluminium reflector
<b>C</b>	Clear cover	<b>M</b>	Matt parabolic louvre
<b>D</b>	Asymmetric reflector	<b>S</b>	SPOT - narrow angle
<b>E</b>	Polished parabolic louvre, high LOR	<b>U</b>	MEDIUM - middle angle
<b>F</b>	FLOOD - wide angle	<b>W</b>	Wide beam angle
<b>I</b>	Microprismatic optical system	<b>Z</b>	Plastic louver, low UGR
<b>K</b>	Opal diffuser		

### Electrical connection

<b>/BT</b>	Luminaires controlled via Bluetooth technology	<b>P</b>	Sensor and electronic ballast
<b>D</b>	DALI dimmable	<b>T</b>	By switch dimmable (touch dimm)
<b>E</b>	Electronic ballast non-dimmable	<b>TD</b>	DALI or by switch (touch dimm) dimmable
<b>M</b>	Electronic ballast non-dimmable with 1h emergency	<b>U</b>	Dimmable luminaire with dimmer on the luminaire
<b>M3</b>	Electronic ballast non-dimmable with 3h emergency		

### Colour

<b>W</b>		<b>RAL 9003</b>	<b>B</b>		<b>RAL 9005</b>	<b>S</b>		<b>TIGER 09/90530</b>
<b>1021</b>		<b>RAL 1021</b>	<b>2000</b>		<b>RAL 2000</b>	<b>3020</b>		<b>RAL 3020</b>
<b>5015</b>		<b>RAL 5015</b>	<b>6018</b>		<b>RAL 6018</b>	<b>7016</b>		<b>RAL 7016</b>
<b>9006</b>		<b>RAL 9006</b>	<b>9010</b>		<b>RAL 9010</b>			

### Značky typu

	Smart – Luminaire or the lighting system controlled by motion, daylight or via smart devices using Bluetooth technology
	Acoustic – Luminaire with acoustic absorption properties which reduce disturbing noise and improve the acoustics of the room
	Multiwatt – Luminaires with individually adjustable luminous flux using a special antenna or mobile application

**UGR** UGR – The luminaire suitable for office spaces